

THERMOCOUPLE & SCR CONTROLLER
SPECIALTY MANUFACTURER
INDUSTRIAL ALLOYS,
FINNACE MATERIALS,
INSTRUMENT & EQUIPMENT

Tel: +603 7980 8940 Fax: +603 7983 8943 http://oneunion.com.my

RTD Teflon Probes with Bakelite Small Head

A1RTD1-T2.5-01



Overview

- All temperature sensors are custom made standard item
 - 100 ohm platinum RTD 3-w ire element
 - Class A accuracy
 - Ø10mm diameter, teflon rod to protect against corrosives environments
 - 63.50mm probe length
- · Connection Head
- Bakelite IP65 screw cover head with gasket
- One turn cover removal & installation eliminates cross threading and saves time
- 3/8"BSP conduit opening with internal stop to prevent overtightening and installation damage
- Gripping ribs on cover edge
- with cover chain
- Wiring
- Ceramic terminal block
- Brass terminals with screws eliminate the need to wrap connections around screws
- Others
- Required others type of thermocouple ,specification & temperature range can be custom made upon request.

RTD Teflon Probes with Bakelite Small Head						
	RTD	Probe Diameter	Probe	Temperature Sensing	Mounting	
Part Number	Type	(O.D)	Length	Range		
A1RTD-T2.5-01	PT-100 3 wire	10mm	63.5mm	-200 to 200°c	Integral 1/4"x1/4"bsp Teflon	

Technical Specifications				
Sensing Element	Single 100 ohm (PT 100), 3 wire			
Initial Accuracy	Class A +/- [0.15 + 0.002 ltl] ° C			
Probe	Ø10mm teflon rod ,single RTD			
Connection Head	Connection Head Bakelite, screw cover with chain, IP65, 3/8"BSP conduit opening			



58200 Kuala Lumpur, Malaysia.

Tel: +603 7980 8940 Fax: +603 7983 8943 http://oneunion.com.my



RTD Teflon Probes with Bakelite Small Head

Dimension

A1RTD1-T2.5-01





TABLE A				
PART NUMBER	U LENGTH			
A1RTD-T2.5-01	63.50mm			

Wiring Information





- · Ignore polarity marks on terminal base
- Recommended screw terminal tightening torque 3-4 lb-in